










## MANTEL SMT-3510

### Hydrogen-rich with alkaline water.

Flow-rate 300-450 Litre/hr.

Dimension : 150W-400L-400H

NO	FILTER	DESCRIPTION
1.		<p>Sediment filter, Material : polypropylene, micron rating :5um            Pressure drop:0.04 bar@20l/min,mix.op.temp: 60 C°            Max op. pressure :45 psi, dimension: id=25.4mm. Od=63 mm.</p>
2.		<p>Resin filter, kastel cl300            Pressure drop:0.05 bar@5l/min,mix.op.temp: 60 C°            Max op. pressure :45 psi, dimension: id=25.4mm. Od=63 mm.</p>
3.		<p>carbon block filter, Material: coconut shell ,micron rating :10um            Pressure drop:0.05 bar@5l/min,mix.op.temp: 60 C°            Max op. pressure :45 psi, dimension: id=25.4mm. Od=63 mm.</p>
4.		<p>Post carbon filter, activate inline ,            mix.op.temp: 50 C°,max flow=0.75 gpm,service life=2,500gall            Max op. pressure :125 psi, dimension: 63mm.</p>
5.		<p>Hydrogen-rich with alkaline water            mix.op.temp: 42 C°,max flow=2.8 lpm,service life=4,000gall            Max op. pressure :125 psi, dimension: 50mm.</p>
6.		<p>Gooseneck faucet and shut-off-valve ,tube Ø¼ inch</p>
7.		<p>Filter wrench.</p>